


ABOX-5000G

Intel 6th-Gen Skylake Core i7/i5/i3 CPU w/ 4 GbE/ 4 ISO COM/ 4 DP/4 USB 3.0 / AMD Radeon™ E9260 GPU/ 9-36V Fanless Computer



Delay Time



Power Ignition



Wide Range



Wireless



Battery Backup

Taiwan Patent No. M447854
Taiwan Patent No. M448011

System

CPU	Intel Gen6 Core i7-6700TE (8M Cache 2.4GHz up to 3.4GHz) Intel Gen6 Core i5-6500TE (6M Cache 2.3GHz up to 3.3GHz) Intel Gen6 Core i3-6100TE (4M Cache 2.7GHz) Intel Pentium Processor G4400TE (3M Cache, 2.40 GHz)
Memory	2 x DDR4 2133 MHz SO-DIMM up to 32GB
Chipset	Intel® Q170 Platform Controller Hub
LAN Chipset	3 x Intel i210-AT and 1 x i219LM (support iAMT) Gb/s Ethernet Controllers Onboard Support PXE and WOL
Watchdog	1 ~ 255 Level Reset

I/O

Serial Port	4 x RS 232/422/485 w/1.5KVrms isolation (Auto Direction Control)
USB Port	4 x USB 3.0 Ports
LAN	4 x RJ45 Ports for GbE (Optional for 4 x POE 15.4W per port)
Video Port	4 x Display Port (Triple Independent Display)
DIO Port	8 x GPI and 4 x GPO connector w/1.5KVrms isolation
Audio	1 x Line-out and 1 x Mic-in (Line-in Optional)
Expansion Bus	3 Full and 1 Half Mini-PCIe Slot (2 x SIM Card Sockets for 3G/LTE)

Graphics

Graphics	AMD Radeon™ E9260 GPU Support for OpenGL 4.5. and OpenCL™ 2.0. Support for Mantle and AMD LiquidVR™ Support for DirectX® 12 (Feature Level 12_0) features
Resolution	Max Resolution (DP1.3) : 5120x2880@60Hz

Storage

Type	1 x 2.5" Drive Bay for SATA Type HDD/SSD 1 x SATA DOM
-------------	--

Features

- Intel® 6th-Gen Quad Core i7 LGA1151 CPU
- 4 x RS-232/422/485 with 1.5KVrms isolated
- 8 x GPI and 4 x GPO with 1.5KVrms isolated
- AMD Embedded Radeon™ E9260 GPU
- Dual Hot Swappable SATA Storage
- 9-36VDC input and operating Temp.: -40 ~ 70°C
- 4 x GbE LAN (optional for 4 x PoE)

Power Requirement

Power Input	9V - 36V DC Power Input
Power Protection	Automatics Recovery Short Circuit Protection
Power Management	Vehicle Power Ignition for Variety Vehicle
Power Off Control	Power off Delay Time Setting by BIOS and Software
Battery (UPS)	Internal Battery Kit for 10 Mins Operating (Optional) Patent No. : M447854 - Build-in Battery

Environmental

Operating Temp.	-40°C ~ 70°C (Default CPU 35Watt)
Storage Temp.	-40°C ~ 80°C
Relative Humidity	0% RH – 95% RH
Vibration(random)	IEC60068-2-64, random, 2.5G@5~500Hz, 1hr/axis with SSD
Vibration Operating	MIL-STD-810G, Method 514.6, Procedure I, Category 4
Shock	Operating: MIL-STD-810G, Method 516.6, Procedure I, Trucks and semi-trailers=15G (11ms) with SSD
Certifications	CE, FCC Class A

Mechanical

Construction	Aluminum Alloy
Mounting	Wall-mount, VESA-mount, Din Rail Mounting Kit
Weight	3860g (Barebone)
Dimensions	240(L) x 226(W) x 79(H) mm

Ordering Information

Part Number	ABOX-5000G-i7S Optional for i5S/i3S/C1S
Description	Intel 6th-Gen Skylake Core i7/i5/i3 CPU w/ 4 GbE/ 4 ISO COM/ 4 DP/ 4 USB 3.0/ AMD Radeon™ E9260 GPU/ 9-36V Fanless Computer