

SBOX-2600

Intel Gen4 Core i7-4650U CPU with HD 5000 GPU / 2xLAN/ HDMI/ DVI/ VGA/ DC 12V Fanless Box PC



- Intel Gen4 CPU
- Win 8/7 Linux
- DDR3L 1600
- DVI/VGA HDMI
- DC 12V
- Dual GbE Lan

Features

- Intel Core i7-4650U / Core i5-4300U
- Triple Display Output (DVI / HDMI / VGA)
- Embedded OS (Win 8 / 7 and Linux)
- Dual Gigabit Ethernet and 2 x RS-232
- Wide Range Operating Temp. : -30~60°C
- Ultra Slim(40mm), Compact Size and Fanless
- DC 12V Power Input

System

CPU	Intel Gen 4 Core i7-4650U 1.7GHz up to 3.3GHz Intel Gen 4 Core i5-4300U 1.9GHz up to 2.9GHz Intel Gen 4 Core i3-4010U 1.7GHz Intel Gen 4 Dual Core Celeron 2980U 1.6GHz
Memory	1 x DDR3L-1600 SO-DIMM up to 8GB
Chipset	N/A
Graphics	Intel HD Graphics
ATA	2 x Serial ATA ports with 6Gb/s HDD Transfer Rate
LAN Chipset	2 x Intel i210-AT Gigabit Ethernet
Watchdog	1 ~ 255 Level Reset

I/O

Serial Port	2 x RS-232 Ports (2 x RS-232/422/485), Optional Max. 4 x RS-232
USB Port	2 x USB 2.0 Ports and 2 x USB 3.0
LAN	2 x RJ45 Ports for GbE
Video Port	HDMI/DVI/VGA(Through DVI-I*)
GPIO Port	4 In and 4 Out GPIO Ports (5V Level)
Audio	Line-Out / Mic-in
Expansion Bus	2 x Mini-card Slots

* Use only with Single Link DVI Cables.

Storage

Type	1 x 2.5" Drive Bay for SATA Type Hard Disk Drive / SSD 1 x SATA DOM
-------------	--

Software

Operating System	Windows 8.1 32/64, Windows 7 32/64, WES 7, Linux 3.8.X
-------------------------	--

Qualification

Certifications	CE, FCC Class A, UL
-----------------------	---------------------

Environmental

Operating Temp.	-30 ~ 60°C, ambient w/ air
Storage Temp.	-40 ~ 85°C
Relative Humidity	10 ~ 95% @ 40°C (non-condensing)
Power Input	DC 12V Input

Mechanical

Construction	Aluminum Alloy
Mounting	Wall-mount, VESA-mount, Din Rail Mounting Kit
Weight	1200g (Barebone)
Dimensions	182 x 167.6 x 40 mm

Ordering Information

Part Number	762600011000 - SBOX-2600-C1 System (C1 can be i3/i5/i7)
Description	Intel Gen4 Core i7-4650U CPU with HD 5000 GPU / 2xLAN/ HDMI/ DVI/ VGA DC 12V Fanless Box PC