

VBOX-3610

Intel Gen5 Core i7-5650U CPU with HD 6000 GPU On-Board Computer



Delay Time



Power Ignition



Wide Range



Wireless



Battery Backup

Taiwan Patent No. M447854
Taiwan Patent No. M448011

System

CPU	Intel Gen 5 Core i7-5650U 2.2GHz up to 3.1GHz Intel Gen 5 Core i3-5010U 2.1GHz Intel Gen 4 Core i7-4650U 1.7GHz up to 3.3GHz Intel Gen 4 Core i5-4300U 1.9GHz up to 2.9GHz Intel Gen 4 Core i3-4010U 1.7GHz Intel Gen 4 Dual Core Celeron 2980U 1.6GHz
Memory	2 x DDR3L 1600 MHz SO-DIMM up to 16GB
Chipset	N/A
LAN Chipset	Intel I210-AT Gb/s Ethernet Controllers Onboard Support PXE and WOL
Audio	Realtek ALC662 HD Codec Onboard
Watchdog	Watchdog Timer Support, Offer 1 – 255 Step

I/O

Serial Port	4 x RS-232 (2 with RS-422/485 (Auto Direction Control))
USB Port	2 x USB 3.0 Ports, 2 x USB 2.0 Ports
LAN	2 x RJ45 Ports for GbE
Video Port	1 x DVI-I, 1 x VGA and 1 x DP (support Triple Independent Display)
DIO Port	4 In and 4 Out
Audio	1 x Line-out and 1 x Mic-in (Line-in Optional)
SIM Card Socket	2 x SIM Card Sockets Supported Onboard with eject

Graphics

Graphics	Intel® HD Graphics 6000 / 5000 DirectX Video Acceleration (DXVA) for Accelerating Video Processing - Full AVC/VC1/MPEG2 HW Decode Supports DirectX 11/10.1/10/9 and OpenGL 4.0
Resolution	Up to 4096 x 2304

Storage

Type	2 x 2.5" Drive Bay for SATA Type HDD/SSD, Support RAID 0, 1 1 x SATA DOM
-------------	---

Features

- Intel Core i7-5650U / Core i3-5010U
- Wireless support LTE, 3.5G w/ Dual SIM Cards, WLAN, GPS Dead Reckoning, GSM/GPRS, BT
- 9V - 36V DC Power Input
- Smarter Vehicle Power Ignition for Variety Vehicle
- Dual Hot Swappable SATA Storage
- 1 x CAN Bus 2.0B (Optional)
- IEC60945 Maritime Certified

Power Requirement

Power Input	9V - 36V DC Power Input
Power Protection	Automatics Recovery Short Circuit Protection
Power Management	Vehicle Power Ignition for Variety Vehicle
Power Off Control	Power off Delay Time Setting by BIOS and Software
Battery (UPS)	Internal Battery Kit for 10 Mins Operating (Optional) Patent No. : M447854 - Build-in Battery

Environmental

Operating Temp.	-40°C ~ 70°C (Default CPU 17Watt)
Storage Temp.	-40°C ~ 80°C
Relative Humidity	0% RH – 95% RH
Vibration(random)	2.5g@5~500 Hz with SSD
Vibration Operating	MIL-STD-810G, Method 514.5, Category 20, Ground Vehicle-Highway
Truck Storage	MIL-STD-810G, Method 514.5, Category 24, Integrity Test
Shock	Operating: MIL-STD-810G, Method 516.5, Procedure I, Trucks and semi-trailers=15G (11ms) with SSD
Crash Hazard	MIL-STD-810G, Method 516.5, Procedure V, Ground equipment=100g
Certifications	CE, FCC Class A, EMark Compliance, EN50155, EN50121, IEC60945 4th Edition, DNV 2.4

Mechanical

Construction	Aluminum Alloy
Mounting	Supports Both of Wall-mount/VESA-mount
Weight	1780 g (Barebone)
Dimensions	250 x 150 x 55 mm

Ordering Information

Part Number	VBOX-3610-i7-5650U
Description	Intel Gen5 Core i7-5650U CPU with HD 6000 GPU On-Board Computer